

Listing of claims:

1. (Original): A mobile device including a computer-readable medium having computer-executable components, comprising:

a router component configured to receive a query document including a query statement related to a setting stored on the computer-readable medium, the router component being further configured to pass at least a part of the query document to other components;

a configuration service provider component associated with the setting and configured to access the setting; and

a configuration manager component configured to receive the at least part of the query document and to identify the configuration service provider based on information within the query document, the configuration manager being further configured to pass the query statement to the configuration service provider for processing.

2. (Original): The computer-readable medium of claim 1, wherein the router component is configured to receive query documents from a plurality of push sources, each push source being configured to interact with an external initiator of the query document.

3. (Original): The computer-readable medium of claim 2, wherein the initiator includes a provisioning server in wireless communication with the mobile device.

4. (Original): The computer-readable medium of claim 2, wherein the initiator includes a provisioning server in wired communication with the mobile device.

5. (Original): The computer-readable medium of claim 1, wherein the configuration service provider is further configured to retrieve a current value of the setting from the computer-readable medium.

6. (Original): The computer-readable medium of claim 5, wherein the configuration manager is further configured to modify the query document based on the retrieved value of the setting.

7. (Original): The computer-readable medium of claim 6, wherein the query statement within the modified query document is modified to include the retrieved value of the setting.

8-19. (Canceled).

20. (Original): A mobile device including a computer-readable medium having computer-executable instructions for performing steps, including:

receiving a configuration message including a payload identifying a particular setting stored on the mobile device;

parsing the configuration message to identify the particular setting stored on the mobile device;

passing the payload to a configuration component responsible for maintaining the particular setting; and

retrieving, by the configuration component, a value associated with the particular setting stored on the mobile device.

21. (Original): The mobile device of claim 20, wherein the computer-readable medium comprises further instructions for returning a response document to an initiator of the configuration message, the response document including the value for the particular setting.

22. (Original): The mobile device of claim 20, wherein passing the payload to the configuration component further comprises identifying which configuration component is responsible for maintaining the particular setting and passing the payload to the identified configuration component.

23. (Original): The mobile device of claim 20, wherein the configuration component comprises a configuration manager programmed to manage a provisioning transaction.

24. (Original): The mobile device of claim 20, wherein the configuration component comprises a configuration service provider responsible for maintaining the particular setting.

25. (Original): A computer-implemented method for querying a setting on a mobile device, comprising:

receiving a configuration message from an initiator, the configuration message including a payload identifying a particular setting stored on the mobile device;

passing at least the payload to a configuration component responsible for maintaining the particular setting;

retrieving, by the configuration component, a value associated with the particular setting stored on the mobile device; and

returning a response document to the initiator of the configuration message, the response document including the retrieved value for the particular setting.

26. (Original): The method of claim 25, wherein passing the payload to the configuration component further comprises identifying which configuration component of a plurality of configuration components is responsible for maintaining the particular setting and passing the payload to the identified configuration component.

27. (Original): The method of claim 25, wherein the configuration component comprises a configuration manager programmed to manage a provisioning transaction.

28. (Original): The method of claim 25, wherein the configuration component comprises a configuration service provider responsible for maintaining the particular setting.

29. (Original): A system for maintaining settings on a mobile device, the system comprising:

a router component configured to receive a query document including a query statement related to a setting stored on the mobile device, the router component being further configured to pass at least a part of the query document to other components on the mobile device; and

a configuration manager component configured to receive the at least part of the query document, to cause the setting to be queried based on the at least part of the query document, and to return results of the query of the setting to the router component.

30. (Original): The system of claim 29, further comprising a configuration service provider component associated with the setting and configured to access the setting, and wherein the configuration manager is further configured to identify the configuration service provider based on information within the query document, and to pass the at least part of the query document to the configuration service provider for processing.

31. (Original): The system of claim 30, wherein the configuration service provider is further configured to retrieve a current value of the setting from the mobile device.

32. (Original): The system of claim 31, wherein the configuration manager is further configured to modify the query document based on the retrieved value of the setting.

33. (Original): The system of claim 32, wherein the query statement within the modified query document is modified to include the retrieved value of the setting.

34. (Original): The system of claim 29, wherein the router component is configured to receive query documents from a plurality of push sources, each push source being configured to interact with an external initiator of the query document.

35. (Original): The system of claim 34, wherein the external initiator includes a provisioning server in wireless communication with the mobile device.

36. (Original): The system of claim 34, wherein the external initiator includes a provisioning server in wired communication with the mobile device.